

BaseLink

H.264/H.265 LIVE STREAMING



Description

Transmit live video from any location and go live on YouTube or other streaming platforms! With the BaseLink you have a live video connection regardless of your location using bonded Fixed, WiFi, 3G and 4G mobile network connections.



Housed in aluminium, BaseLink is made up of four modems, and bundles up to nine mobile network channels and one fixed IP connection to provide sufficient upstream bandwidth for HD video. There is also the option to add Wi-Fi and ethernet connections to maximize bandwidth and ensure high quality video is streamed. BaseLink's upstream bandwidth ranges between 125Kbps and 12 Mbps.

Specifications

INTERFACES

- 1x Ethernet 10/100/1000 base-t
- SD;SD- SDI,SD-HDMI & 2x analog audio
- WiFi
- Audio return
- Touch screen

INPUTS

- SD; full D1, Pal and NTSC mode
- HD; 720p50, 720p60 and 720p59,94
- HD; 1080i50, 1080i60 and 1080i59,94, 1080P60

SUPPORTED ENCODING

- H.264 main profile MVP codec
- H.265 main profile MVP codec
- Framerate 50, 60, 59,94

CONNECTIONS

- 4 Modems, LTE(4G), fallback 3G by default
- Upgradable to 8 modems
- WiFi

INTERNET ACCESS

- Via WiFi
- Via Ethernet

HARDWARE

- Dedicated appliance 12-24 volt
- Weighs approximately 1,2 kilograms
- 20cm x 13cm x 8cm (W x B x H)

OPERATIONS SETTINGS

- Live
- Delay between 1.0 seconds and 10 minutes
- SD/HD

AERIALS

- Dome Antenna;
Omnidirectional Array3 dBi

INCLUDES

- 4 times 3dBi gain; upgradable to 8
- depending on number of modems
- Industry standard battery plate (Anton)
- Bauer or V-Lock)
- PSU 90-220 Volt AC to 12 Volt DC

ADDITIONAL ACCESOIRES

- Custom made backpack

