

BaseLink

H.264/H.265 LIVE STREAMING



Description

Transmit live video from any location and go live on YouTube or other streaming platform with the BaseLink low-cost streaming solution from Mobile Viewpoint. BaseLink gives you a live video connection regardless of your location using bonded fixed, WiFi, 3G and 4G mobile network connections.



Housed in aluminium, BaseLink contains four modems and can bundle up to nine mobile network channels and one fixed IP connection to provide the upstream bandwidth required for HD video. There is also an option to add WiFi and Ethernet connections to maximize bandwidth and ensure the highest-quality video streaming. BaseLink's upstream bandwidth ranges between 125 Kbps and 12 Mbps.

Specifications

INTERFACES

- 1x Ethernet 10/100/1000 base-t
- SD: SD-SDI
- WiFi
- Audio return
- Touch screen

INPUTS

- SD; full D1, PAL and NTSC mode
- HD: 720p50, 720p60 and 720p59, 94
- HD: 1080i50, 1080i60 and 1080i59, 94, 1080P60

SUPPORTED ENCODING

- H.264 main profile MVP codec
- H.265 main profile MVP codec
- Frame rates: 50, 60, 59, 94

CONNECTIONS

- 4 Modems, LTE(4G), fallback 3G by default
- Upgradable to 6 modems
- WiFi

INTERNET ACCESS

- WiFi
- Ethernet

HARDWARE

- Dedicated appliance 12-24 volt
- Weighs approximately 1.2 kg
- 20 cm x 13 cm x 8 cm (WxDxH)

OPERATIONS SETTINGS

- Live
- Delay between 1.0 seconds and 10 minutes
- SD/HD

AERIALS

- Dome Antenna;
Omnidirectional Array3 dBi

INCLUDES

- 4 times 3dBi gain; upgradable to 8 depending on number of modems
- Industry standard battery plate (Anton Bauer or V-Lock)
- PSU 90-220 Volt AC to 12 Volt DC

ADDITIONAL ACCESSORIES

- Custom made backpack

